

Stylish POS Terminal

TITAN S series

Style added on Performance
the new TITAN

- Intel Celeron N2807, N3160 and J1900 CPU
- Energy Efficient and Low Heat Generation Architecture
- Slim Display, Sleek Chassis and Small Footprint Design
- 15" LED LCD Display with True-Flat PCAP Touch
- IP55 dust and water Proof Front Panel
- Superior Serviceability and Easy Installation
- Fanless Operation and No Ventilation Hole
- Variety ways of Storage Devices : mSATA/m.2/SATAIII 2.5"
- Microsoft Azure Certified



KEY FEATURE



OPTION



PERIPHERAL



SAM4S

Shinheung Precision Co.,Ltd. / Seoul Office

9F, Flat-C, Woolim Lion's Valley, Gasan Digital 1Ro 168, Geumcheon-gu, Seoul, 08507, Korea
Tel, +82-2-2101-9623 | Fax, +82-2-2101-9690 | www.sam4s.com

SPECIFICATION

Model		TITAN-S100	TITAN-S200	TITAN-S300
System	CPU	Intel Celeron N2807 (Dual Core up to 2.16GHz)	Intel Celeron N3160 (Quad Core up to 2.24GHz)	Intel Celeron J1900 (Quad Core up to 2.4GHz)
	Storage	HDD:500GB SSD:256GB/128GB/64GB mSATA:256GB/128GB/64GB	HDD:500GB SSD:256GB/128GB/64GB M.2:256GB/128GB/64GB	HDD:500GB SSD:256GB/128GB/64GB mSATA:256GB/128GB/64GB
	RAM	DDRⅢ1Slot (Up to 4GB)	DDRⅢ1Slot (Up to 8GB)	DDRⅢ1Slot (Up to 8GB)
Display	LCD	15" LED Backlight LCD (1024 x 768)		
	Touch	PCAP Touch/5W Resistive Touch		
Interface	Serial	3 Ports (RS-232 RI/5V/12V BIOS Selectable) (1 Port:RS-422/485 (Jumper Selectable))		
	Parallel	4 Ports Option is Available		
	USB	1 Port (Optional)		
	Ethernet	6 Ports		
	VGA	1 Port		
	Drawer	1 Port/2 CH (12V/24V Selectable)		
	Audio	1 Port (Line out)		
Optional	MSR	1/2/3 Track Support (USB)		
	Rear Display	VFD (20 CH x 2 line, 256 x 32 Graphic) LED LCD (9.7",15" (Touch Option))		
	Wall Mount	VESA Wall Mount		
	Stand	V Stand		
Software	OS	POSReady 7/Windows 7, 8.1, 10/Windows 10 IoT		
Power Supply		DC 12V/5A(60W)		
Dimensions		379(W) x 264(H) x 362(D)mm		
Weight		6.0kg		
Color		Black + White, Black, White		
Certifications		CE/FCC/CB/cTUVus(NRTL)/RoHS		

*Without any prior notice, design and specification are subject to change.

INTERFACE VIEW

